

SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#1/21

In conformity to Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name: SANIFOAM

Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

Chloroactive alkaline detergent

Sectors of use:

Industrial Manufacturing[SU3], Manufacture of food products[SU4], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Washing and Cleaning Products (including solvent based products)

Process categories:

Industrial spraying[PROC7], Transfer of substance or mixture (charging and discharging) at nondedicated facilities[PROC8A], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Non industrial spraying[PROC11]

Not recommended uses Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy

Tel. +39.030.2307.1 Fax +39.030.2307281

E-mail: info@aeb-group.com - Internet: www.aeb-group.com E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA 111 N Cluff Avenue Lodi CA 95240 (USA)

Tel: +1 2096258139 Fax: +1 2092248953

Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD 18 Track Crescent, Cor. Station Road Montague Gardens 7441 Cape Town (South Africa)

Tel.: +27 215512700 - Fax: +27 (0) 215511919

Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD 178A Wakaden Street Griffith NSW 2680

T: 1300 704 971

Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by AEB SpA Via Vittorio Arici 104 S. Polo



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#2/21

In conformity to Regulation (EU) 2020/878

25134 Brescia

1.4. Emergency telephone number

AEB SpA

Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD

Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD

Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05, GHS09

Hazard Class and Category Code(s):

Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2

Hazard statement Code(s):

H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H400 - Very toxic to aquatic life. (Acute toxicity M-factor = 1)

H411 - Toxic to aquatic life with long lasting effects.

The product can be corrosive to metals

Corrosive product: causes severe skin burns and eye damage.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

The product is dangerous for the environment as it is very toxic to aquatic organisms

The product is dangerous to the environment as it is toxic to aquatic life with long lasting effects

2.1.2 Additional information:

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s): GHS05, GHS09 - Danger







SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#3/21

In conformity to Regulation (EU) 2020/878

Hazard statement Code(s):

H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

H410 - Very toxic to aquatic life with long lasting effects.

Supplemental Hazard statement Code(s):

EUH031 - Contact with acids liberates toxic gas (CI2).

Precautionary statements:

Prevention

P260 - Do not breathe vapours/spray.

P280 - Wear protective gloves/clothing and eye/face protection.

Response

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal

P501 - Dispose of contents/container to local/regional/national/international regulations

Contains:

Sodium hydroxide, Sodium hypochlorite

Contains (Reg.EC 648/2004):

>= 5% < 15% chlorine-based bleaching agents, < 5% non-ionic surfactants, polycarboxylates

2.3. Other hazards

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

The use of this chemical agent implies the obligation of the "risk assessment" by the employer according to the provisions of Legislative Decree April 9, 2008 no. 81 and subsequent amendments. If the results of the risk assessment demonstrate that, in relation to the type, quantity, methods and frequency of exposure, there is only a low risk for the safety and irrelevant for the health of the workers and that the measures referred to in paragraph 1 of Legislative Decree April 9, 2008 no. 81 are sufficient to reduce the risk, the provisions of articles 225, 226, 229, 230 of the same Legislative Decree do not apply

Do not ingest. Keep out of reach of children.

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#4/21

In conformity to Regulation (EU) 2020/878

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
Sodium hydroxide	>= 5 < 10%	Met. Corr. 1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Limits: Skin Corr. 1A, H314 %C >=5; Skin Corr. 1B, H314 2<= %C <5; Eye Irrit. 2, H319 0,5<= %C <2; Eye Dam. 1, H318 %C >=2; Skin Irrit. 2, H315 %C >=0,5;	011-002-00-6	1310-73-2	215-185-5	01-2119457 892-27-XXX X
Sodium hypochlorite (B)	>= 5 < 10%	EUH031; Met. Corr. 1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Limits: , EUH031 %C >=5; Acute toxicity M-factor = 10 Chronic toxicity M-factor = 1	017-011-00-1	7681-52-9	231-668-3	01-2119488 154-34-XXX X
Amines, C12-14 alkyldimethyl, N-oxides	>= 1 < 2,5%	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute toxicity M-factor = 1 Chronic toxicity M-factor = 1 ATE oral = 500,000 mg/kg		308062-28-4	931-292-6	01-2119490 061-47-XXX X
2-Propenoic acid, homopolymer, sodium salt substance for which there are Community workplace exposure limits	>= 0,1 < 1%			9003-04-7		Polymer

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of skin contact: Immediately take off all contaminated clothing and dispose of them in a safe way. SEE A DOCTOR IMMEDIATELY. In case of contact with skin, wash immediately with plenty of water and soap. In case of contact with the eyes: rinse them with water for an adequate time and keeping the eyelids open, then immediately consult an ophthalmologist. Protect the uninjured eye.

In case of ingestion: DO NOT induce vomiting.

In case of inhalation: take the injured person to fresh air and keep him warm and at rest

4.2. Most important symptoms and effects, both acute and delayed

Inhalation can produce a burning sensation, cough, difficulty breathing and sore throat. Contact with the skin produces redness, burns and pain. Contact with eyes produces severe redness, pain and deep burns. Ingestion causes severe irritation or chemical burns in the mouth, throat, esophagus and stomach.



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#5/21

In conformity to Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, consult a doctor immediately (if possible show the instructions for use or the safety data sheet). Treatment: The severity of injuries and the prognosis of intoxication are directly dependent on the concentration and duration of exposure. Symptomatic treatment

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suggested extinguishing media:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing media to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

Do not inhale the gases produced by the explosion and combustion

5.3. Advice for firefighters

Use suitable respiratory equipment. Collect contaminated water used to extinguish the fire separately. Do not discharge it into the sewer system. If feasible from a safety perspective, move undamaged containers from the area of immediate danger

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Move away from the area surrounding the spill or release. Not smoking. Wear a mask, gloves and protective clothing.

6.1.2 For emergency responders:

Eliminate all open flames and possible sources of ignition. Not smoking. Provide adequate ventilation. Evacuate the danger area and, if necessary, consult an expert.

6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities. Dispose of the waste material in compliance with the regulations



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#6/21

In conformity to Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS) Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert materia or sucked it. Prevent it from entering the sewer system.

6.3.2 Cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

Wash with plenty of water

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Wear protective gloves/clothing and eye/face protection.

Handle the product after consulting all other sections of this safety data sheet.

At work do not eat or drink.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with care. Store in a well-ventilated place, away from heat sources and in the original well-closed containers. Follow the attached exposure scenarios

Manufacture of food products:

Handle with care.

Store in a clean, dry, ventilated area away from heat and direct sunlight.

Keep container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a well-ventilated place, away from heat sources and in the original well-closed containers. Follow the attached exposure scenarios

•

See the annex exposure scenario.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

Sodium hydroxide:

Limit value – Eight hours



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#7/21

In conformity to Regulation (EU) 2020/878

(ppm)/(mg/m3)

Austria: x/2 inhalable aerosol

Belgium: x/2 (1) Denmark: x/2 France: x/2 Hungary: x/2

Japan (JSOH): x/2(1)

Latvia: x/0,5 Poland: x/0,5 Romania: x/1 Spain: x/2 Sweden: x/1 (1)

Switzerland: x/2 inhalable aerosol (MAK)

USA - OSHA: x/2

Limit Value - Short Term

(ppm)/(mg/m3) Austalia: x/2(1)

Austria: x/4 inhalable aerosol Canada - Ontario: x/2(1) Canada – Québec: x/2(1)

Denmark: x/2 Finland: x/2(1) Hungary: x/2 Ireland: x/2(1) New Zealand: x/2(1)

People's Republic of China: x/2(1)

Poland: x/1 Romaniax/3(1) Singapore: x/2 South Korea: x/2(1) Sweden: x/2(1)(2)

Switzerland: x/2 inhalable aerosol (MAK)

USA – NIOSH: x/2(1) United Kingdom: x/2

Remarks:

Australia: (1) Celling limit value

Canada – Ontario: (1) Celling limit value Canada – Québec: (1) Celling limit value

Finland: (1) Celling limit value

Ireland: (1) 15 minutes reference period

Japan: (1) Occupational exposure limit ceiling: Reference value to the maximal exposure concentration of the

substance during a working day New Zealand: (1) Celling limit value

People's Republic of China: (1) Celling limit value

South Korea: (1) Celling limit value Romania: (1) 15 minutes average value

Sweden: (1) Inhalable dust (2) Celling limit value USA – NIOSH: (1) Celling limit value (15 min)

Argentine: CMP-C: 2 mg mg/m3

Czech Republic: PEL 1 mg/m3/ NPK-P 2 mg/m3

Italy: OEL: ACGIH -STEL: C 2.0 mg/m3; Tipo OEL: ACGIH - STEL: C2 mg/m3 - Note: URT, eye, and skin irr

Estonia: short-term esposure limit (maximum chemical substance average allowable concentration in inhaled air - 15 minutes) 2 mg/m3(Ceiling limit" means a maximum permissible continuous concentration of 15 minutes in the air for rapidly acting substances)

Norvay: ceiling value (a moment value that indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded) 2 mg/m3

Lithuania: NRD 2 mg/m3



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#8/21

In conformity to Regulation (EU) 2020/878

Slovakia: NPEL 2 mg/m3

South Africa: Short Term OEL-CL 2 mg/m³

Sodium hypochlorite:

Substance: Chlorine (CAS 7782-50-0)

Limit value - Eight hours

(ppm)/(mg/m³)

Austria: 0,5/1,5

Canada – Ontario: 0,5/-Canada - Québec: 0,5/1,5

Denmark: 0,5/1,5

Germany (AGS): 0,5/1,5 Germany (DFG): 0,5/1,5

Israel: 0,5/1,5 Japan: 0,5/x

Japan - JSOH: 0,5(1)/1,5(1)

Latvia: 0,3/1

New Zealand: 0,5/1,5

Poland: x/0,7 Singapore: 0,5/1,5 South Korea: 0,5/1,5 Switzerland: 0,5/1,5

Limit value - Short term

 $(ppm)/(mg/m^3)$

Australia: 1(1)/3(1) Austria: 0,5/1,5 Belgium: 0,5/1,5 Canada – Ontario: 1/-Canada - Québec: 1/2,9

Denmark: 1/3

European Union: 0,5(1)/1,5(1)

Finland: 0,5(1)/1,5(1) France: 0,5/1,5

Germany (AGS): 0,5(1)/1,5(1) Germany (DFG): 0,5/1,5

Hungary: x/1,5 Italy: 0,5/1,5 Latvia: 0,5(1)/1,5(1) New Zealand: 1/2,9

People's Republic of China: x/1(1)

Poland: x/1,5

Romania: 0,5(1)/1,5(1) Singapore: 1/2,9 South Korea: 1/3 Spain: 0,5/1,5

Sweden: 0,5(1)/1,5(1) Switzerland: 0,5/1,5 The Netherlands: x/1,5 Turkey: 0,5(1)/1,5(1) USA-NIOSH: 0,5(1)/1,42(1) USA-OSHA: 1(1)/3(1) United Kingdom: 0,5/1,5

Remarks



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#9/21

In conformity to Regulation (EU) 2020/878

Australia - People's Republic of China - USA-NIOSH: 1) Ceiling limit value

European Union: Bold-type: Indicative Occupational Exposure Limit Values and Limit Values for Occupational Exposure Binding Occupational Exposure Limit Value - BOELV ~ (1) 15 minutes average value (for references see bibliography)

Finland - Germany (AGS) - Latvia- Romania - Turkey: (1) 15 minutes average value

France: Bold type: Restrictive statutory limit values Germany (DFG): STV 15 minutes average value

Ireland: (1) 15 minutes reference period

Japan – JSOH: (1) Occupational exposure limit ceiling: Reference value to the maximal exposure concentration of the

substance during a working day Sweden: (1) Short-term limit value

2-Propenoic acid, homopolymer,

sodium salt:

TWA respirable dust fraction (DOW IHG): 0,5 mg/m3

- Substance: Sodium hydroxide

DNEL

Systemic effects Short term Workers inhalation = 1 (mg/m3)

Systemic effects Short term Consumers inhalation = 1 (mg/m3)

Local effects Short term Workers inhalation = 1 (mg/m3)

Local effects Short term Consumers inhalation = 1 (mg/m3)

- Substance: Sodium hypochlorite

DNEL

Systemic effects Long term Workers inhalation = 1,55 (mg/m3)

Systemic effects Long term Consumers inhalation = 1,55 (mg/m3)

Systemic effects Short term Workers inhalation = 3,1 (mg/m3)

Systemic effects Short term Consumers inhalation = 3,1 (mg/m3)

Local effects Long term Workers inhalation = 1,55 (mg/m3)

Local effects Long term Consumers inhalation = 1,55 (mg/m3)

Local effects Short term Workers inhalation = 3,1 (mg/m3)

Local effects Short term Consumers inhalation = 3,1 (mg/m3)

PNEC

Sweet water = 0,00021 (mg/l)

Sea water = 0,000042 (mg/I)

STP = 0.03 (mg/l)

- Substance: Amines, C12-14 alkyldimethyl, N-oxides

DNFI

Systemic effects Long term Workers inhalation = 6,2 (mg/m3)

Systemic effects Long term Workers dermal = 11 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 1,53 (mg/m3)

Systemic effects Long term Consumers dermal = 5,5 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 0,44 (mg/kg bw/day)

PNEC

Sweet water = 0.0335 (mg/l)

sediment Sweet water = 5,24 (mg/kg/sediment)

Sea water = 0,00335 (mg/I)

sediment Sea water = 0,524 (mg/kg/sediment)

STP = 24 (mg/l)

ground = 1,02 (mg/kg ground)



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#10/21

In conformity to Regulation (EU) 2020/878

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection

Wear protective goggles (EN 166).

- (b) Skin protection
- (i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

During working operation wear protective clothing (generic workwear / antacid, safety shoes or other protective equipment) according to the instructions of the employer.

(c) Respiratory protection

Not needed for normal use.

None required if airborne concentrations are maintained below the exposure limit listed in

Exposure Limit Information. During manual operations in case of insufficient ventilation, use mask with gas filters and inorganic vapors - Grey , Class 3 , B (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic

(d) Thermal hazards No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Physical state	clear, slightly viscous liquid	
Colour	Yellow	
Odour	characteristic of chlorine	
Odour threshold	not determined as considered not relevant for the characterization of the product	
Melting point/freezing point	not determined as considered not relevant for the characterization of the product	



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

11 / 21

In conformity to Regulation (EU) 2020/878

Physical and chemical properties	Value	Determination method
Boiling point or initial boiling point and boiling range	not determined as considered not relevant for the characterization of the product	
Flammability	not determined as considered not relevant for the characterization of the product	
Lower and upper explosion limit	not determined as considered not relevant for the characterization of the product	
Flash point	not determined as considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as considered not relevant for the characterization of the product	
Decomposition temperature	not determined as considered not relevant for the characterization of the product	
рН	> 12 (20°C) ; > 12 (20°C ; sol. 6%)	
Kinematic viscosity	not determined as considered not relevant for the characterization of the product	
Solubility	in water	
Water solubility	miscible in all proportions	
Partition coefficient n-octanol/water (log value)	not determined as considered not relevant for the characterization of the product	
Vapour pressure	not determined as considered not relevant for the characterization of the product	
Density and/or relative density	1,2 ± 0,05 (20 °C)	
Relative vapour density	not determined as considered not relevant for the characterization of the product	
Particle characteristics	not determined as considered not relevant for the characterization of the product	

9.2. Other information

9.2.1 Information with regard to physical hazard classes

Irrilevant

9.2.2 Other safety characteristics

Irrilevant

SECTION 10. Stability and reactivity

10.1. Reactivity

Mixture containing sodium hypochlorite. It can be corrosive to metals. It is not pyrophoric.

10.2. Chemical stability

Stable under the indicated conditions of use and storage



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#12/21

In conformity to Regulation (EU) 2020/878

10.3. Possibility of hazardous reactions

Exothermic reaction with acids, amines

10.4. Conditions to avoid

Light, heat.

10.5. Incompatible materials

Acids Amines Metals Combustible materials

10.6. Hazardous decomposition products

Toxic gas (chlorine)

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATE(mix) oral = 37.004,1 mg/kg

(a) acute toxicity: Sodium hydroxide: Ingestion - LD50 rat (mg / kg / 24h bw): nd

Skin contact - LC50 rabbit (mg / kg / 24h bw): 1350

Inhalation - LD50 rat (mg / I / 4h): nd

Sodium hypochlorite: Ingestion - LD50 rat (mg / kg / 24h bw):> 5000

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw):> 20000

Inhalation - LD50 rat (mg / I / 4h):> 10, 5

Amines, C12-14 alkyldimethyl, N-oxides: Skin contact - LC50 rat / rabbit (mg / kg / 24h bw): na

Inhalation - LD50 rat (mg / I / 4h): na

2-Propenoic acid,

homopolymer,

sodium salt: Ingestion - LD50 rat (mg / kg / 24h bw):> 5000

Contact with skin - LD50 rabbit (mg / kg / 24h bw):> 2000

Inhalation - LC50 rat (mg / I / 4h): nd

(b) skincorrosion/irritation: Corrosive product: causes severe skin burns and eye damage.

Sodium hydroxide: Corrosive Sodium hypochlorite: Corrosive

Amines, C12-14 alkyldimethyl, N-oxides: Non-corrosive

2-Propenoic acid,



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#13/21

In conformity to Regulation (EU) 2020/878

homopolymer,

sodium salt: Non-corrosive Sodium hydroxide: Irritating Sodium hypochlorite: Irritating

Amines, C12-14 alkyldimethyl, N-oxides: Irritating

2-Propenoic acid, homopolymer,

sodium salt: Slightly irritating

(c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Sodium hydroxide: Corrosive Sodium hypochlorite: Corrosive

Amines, C12-14 alkyldimethyl, N-oxides: Corrosive

2-Propenoic acid, homopolymer,

sodium salt: Non-corrosive Sodium hydroxide: Irritating Sodium hypochlorite: Irritating

Amines, C12-14 alkyldimethyl, N-oxides: Irritating

2-Propenoic acid, homopolymer,

sodium salt: Slightly irritating

(d) respiratoryorskinsensitisation: Sodium hydroxide: Not sensitizing

Sodium hypochlorite: Not sensitizing

Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid, homopolymer,

sodium salt: Non-sensitizing

(e) germ cell mutagenicity: Sodium hydroxide: NaOH did not induce mutagenicity in in vitro and in vivo studies (EU RAR, 2007; section 4.1.2.7, page 73).

Sodium hypochlorite: Not mutagenic

Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid, homopolymer,

sodium salt: Non-mutagenic

(f) carcinogenicity: Sodium hydroxide: Systemic carcinogenicity is not expected to occur as NaOH is not expected to be systemically available in the body under normal conditions of handling and use. Finally, adequate studies are not available to assess the risk on local carcinogenic effects.

Sodium hypochlorite: Not carcinogenic

Amines, C12-14 alkyldimethyl, N-oxides: NOAEL 200 mg/kg, Oral, Rat REACH dossier information. Based on available data, the classification criteria are not met.

2-Propenoic acid,

homopolymer,

sodium salt: Non-carcinogenic

(g) eproductivetoxicity: Sodium hydroxide: NaOH is not expected to be systemically available in the body under normal conditions of handling and use and for this reason it can be said that the substance will neither reach the fetus nor reach the male and female reproductive organs (EU RAR Sodium Hydroxide (2007), section 4.1.2.8, page 73). It can be concluded that a specific study is not required to determine reproductive toxicity.

Sodium hypochlorite: Non-toxic for reproduction Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid,

homopolymer,

sodium salt: Not available

(h) specific target organ toxicity (STOT) single exposure: Sodium hydroxide: The substance can be absorbed into the body by inhalation of its aerosol, by ingestion and by contact with the skin causing corrosion

Sodium hypochlorite: It can be irritating to the respiratory tract

Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid, homopolymer,



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#14/21

In conformity to Regulation (EU) 2020/878

sodium salt: Not available

(i) specific target organ toxicity (STOT) repeated exposureSodium hydroxide: The introductory sections of Annexes VII-X indicate a specific adaptation to standard information requirements as in vivo testing should be avoided with corrosive substances at concentration / dose levels causing corrosivity. However, NaOH is not expected to be systemically available in the body under normal conditions of handling and use and therefore no systemic effects of NaOH are expected after repeated exposure (EU RAR sodium hydroxide (2007); section 4.1.3.1.4, page 76).

Sodium hypochlorite: Not classified

Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid.

homopolymer,

sodium salt: Not available

(j) aspiration hazard: Sodium hydroxide: Not available

Sodium hypochlorite: Not available

Amines, C12-14 alkyldimethyl, N-oxides: Not available

2-Propenoic acid, homopolymer,

sodium salt: Not available

===============

Related to contained substances: Amines, C12-14 alkyldimethyl, N-oxides: LD50 (rat) Oral (mg/kg body weight) = 500

11.2. Information on other hazards

No data available.

11.2.1. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Sodium hydroxide:

Acute toxicity - fish LC50 (mg / I / 96h): 45

Acute toxicity - crustaceans EC50 (mg / I / 48h): 40 Acute toxicity to algae ErC50 (mg / I / 72-96h): n.d

Chronic toxicity - fish NOEC (mg / I): n.d

Chronic toxicity - crustaceans NOEC (mg / I): n.d

Chronic toxicity to algae NOEC (mg / I): n.d

Available data indicate that NaOH concentrations of approximately 20 to 40 mg / L may be acutely toxic to fish and invertebrates (single species test). There is a lack of data on the increase in pH due to the addition of these quantities of NaOH in the test waters used. In waters with relatively low buffering capacity, NaOH concentrations of 20-40 mg / L may lead to an increase in pH with one or more pH units (EU RAR, 2007; section 3.2.1.1.3, page 30).

The OECD SIDS (2002) assigned a low reliability code ("invalid" or "not assignable") to all available tests, since in general the tests were not conducted according to current guidelines (EU RAR, 2007; section 3.2, 1.1.4, page 30). Furthermore, in many test reports there were no data on pH, buffer capacity and / or composition of the test medium. although this is essential information for NaOH toxicity testing. This is the most important reason why most of the tests were considered "invalid". Despite this lack of valid data, it is not necessary to perform further aquatic toxicity tests with NaOH, as all available tests have resulted in a rather small range of toxicity values (acute toxicity test: 20 to 450 mg / L; test chronic toxicity:> or = 25 mg / L) and there are sufficient data on the pH ranges tolerated by the main taxonomic



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

15 / 21

In conformity to Regulation (EU) 2020/878

groups.

Furthermore, a generic PNEC cannot be derived from the single species toxicity data for NaOH, as the pH of natural waters and the buffering capacity of natural waters show considerable differences and aquatic organisms / ecosystems are adapted to these specific natural conditions, with resulting in different pH optima and tolerated pH ranges (EU RAR, 2007; section 3.2.1.1.4, page 30). According to the OECD SIDS (2002), a lot of information is available on the relationship between pH and ecosystem structure, and natural changes in the pH of aquatic ecosystems have also been quantified and widely reported in ecological publications and manuals.

C(E)L50 (mg/l) = 45 Acute toxicity M-factor = 1

Chronic toxicity M-factor = 1

Sodium hypochlorite:

cute toxicity - LC50 freshwater fish (mg / I / 96h): 0.060 Acute toxicity - LC50 seawater fish (mg / I / 96h): 0.032

Acute toxicity - Daphnie EC50 (mg / I / 48h): 0.048

Acute toxicity - Daphnia Magna, fresh water EC50 (mg / I / 48h): 0.141 Acute toxicity - Ceriodaphnia dubia, fresh water EC50 (mg / I / 48h): 0.035 Acute toxicity - Cassostrea Virginica, sea water EC50 (mg / I / 48h): 0.026

Acute toxicity ErC50 algae (mg / I / 72-96h): 0.0183

Acute toxicity - Pseudokirchnerella subcapitata EC50 (mg / I / 96h): 0.04 Acute toxicity - Myriophyllum spicatum, fresh water EC50 (mg / I / 96h): 0.1

Chronic toxicity - fish, sea water NOEC 28 die (mg / I): 0.04

Chronic toxicity - crustaceans NOEC 7 die (mg / I): 0,007 (oyster)

Chronic toxicity Pseudokirchnerella subcapitata ErC10 (mg / I): 0.03

Chronic toxicity Pseudokirchnerella subcapitata NOEC (mg / I): 0.017

Chronic toxicity Periphyton algae, fresh water, NOEC 7 die (mg / I): 0.0021

Toxicity, sediment compartment: not classified Toxicity of the terrestrial compartment: not calssified C(E)L50 (mg/l) = 0,06 Acute toxicity M-factor = 10 Chronic toxicity M-factor = 1

Amines, C12-14 alkyldimethyl, N-oxides:

Acute toxicity - fish LC50 (mg / I / 96h): 2.67

Acute toxicity - crustaceans (Daphnia magna) EC50 (mg / I / 48h): 3.1

Acute algae toxicity - ErC50 (mg / I / 72h): 0.66

Chronic toxicity - fish NOEC (mg / I / 302d): 0.42

Chronic toxicity - crustaceans (Daphnia magna) NOEC (mg / I / 21d): 0.7

Chronic toxicity - algae NOEC (mg / I / 28d): 0.067

C(E)L50 (mg/l) = 0,66 Acute toxicity M-factor = 1

NOEC (mg/l) = 0.067 Chronic toxicity M-factor = 1

2-Propenoic acid,

homopolymer,

sodium salt:

LC50, Oncorhynchus mykiss (Rainbow trout), 96 h, 700 mg / I

EC50, Daphnia magna (Water flea), 48 h,> 1 000 mg / I

EC50, Marine algae (Skeletonema costatum), 72 h, Speed of growth, 480 mg / I

For similar material (s)

(NOEC), Daphnia magna (Large water flea), Continuous flow test, 21 d, number of offspring, 12 mg / I

For similar material (s)

MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Large water flea), Continuous flow test, 21 d, number of descendants, 17 mg / I



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

16 / 21

In conformity to Regulation (EU) 2020/878

Information on a similar product: CL50, Eisenia fetida (earthworms), 14 days,> 1 000 mg / kg Acute toxicity M-factor = 1 Chronic toxicity M-factor = 1

The product is dangerous for the environment as it is very toxic to aquatic organisms following acute exposure. The product is dangerous for the environment as it is toxic to aquatic organisms following acute exposure.

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability

Related to contained substances:

Sodium hydroxide:

according to REACH regulation, it is not necessary to conduct the study if the substance is inorganic (Annex VII, adaptation column 2).

Sodium hypochlorite:

Not applicable. It is a strong oxidant. Reacts with organic substances of soil and sediment degrading rapidly.

Amines, C12-14 alkyldimethyl, N-oxides:

Easily biodegradable

2-Propenoic acid, homopolymer,

sodium salt:

The material is expected to biodegrade very slowly (in the environment). It does not pass the OECD / EEC tests for rapid biodegradability.

12.3. Bioaccumulative potential

Related to contained substances:

Sodium hydroxide:

According to REACH, it is not necessary to conduct the study if the substance has a low bioaccumulation potential (Annex IX, adaptation column 2). Considering its high water solubility, NaOH should not bioconcentrate in organisms. Log Pow is not applicable for an inorganic compound that dissociates (EU RAR 2007, section 3.1.1 page 19 and section 3.1.3.4, page 26). Furthermore, sodium is an element present in nature prevalent in the environment and to which organisms are regularly exposed, for which they have a certain ability to regulate the concentration of the organism.

Sodium hypochlorite: Non-bioaccumulative LogP (calculated) = -3.42

Amines, C12-14 alkyldimethyl, N-oxides:

log Pow: <2.7

2-Propenoic acid, homopolymer, sodium salt: Not available



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#17/21

In conformity to Regulation (EU) 2020/878

12.4. Mobility in soil

Related to contained substances:

Sodium hydroxide:

According to the REACH regulation, it is not necessary to conduct an adsorption / desorption study if, based on the physicochemical properties, the substance can be expected to have a low adsorption potential (Annex VIII, adaptation column 2).

Considering its high water solubility, NaOH should not bioconcentrate in organisms. The high water solubility and low vapor pressure indicate that NaOH will be found primarily in the aquatic environment.

The 73% aqueous NaOH solution at room temperature is a highly viscous gelatinous material and without additional dilution (precipitation), it is not expected to infiltrate the soil to any significant extent. The 50% aqueous NaOH solution is liquid and is expected to infiltrate the soil to a measurable extent. As a dilution of NaOH

increases, increases its speed of movement through the ground. During movement through the ground, some ion exchange will occur.

Also, part of the hydroxide can remain in the aqueous phase and will move down through the soil in the direction of groundwater flow (EU RAR 2007, section 3.1.3, page 24).

Sodium hypochlorite:

Mobile in soil and sediments

Amines, C12-14 alkyldimethyl, N-oxides: Easily absorbed into the soil.

2-Propenoic acid, homopolymer, sodium salt: Not available

12.5. Results of PBT and vPvB assessment

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

12.6. Endocrine disrupting properties

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

12.7. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (I) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

18 / 21


In conformity to Regulation (EU) 2020/878

according to local and National rules in force

SECTION 14. Transport information

14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 3266



14.2. UN proper shipping name

ADR/RID/IMDG: LIQUIDO INORGANICO CORROSIVO, BASICO, N.A.S. (Sodio ipoclorito e Sodio idrossido in miscela) ADR/RID/IMDG: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hypochlorite and Sodium hydroxide in mixture)

ICAO-IATA: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hypochlorite and Sodium hydroxide in mixture)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class: 8

ADR/RID/IMDG/ICAO-IATA: Label: 8 + ENVIRONMENTALLY HAZARDOUS

ADR: Tunnel restriction code: E

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS: F-A, S-B

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is environmentally hazardous IMDG: Marine polluting agent : Yes

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

#19/21

In conformity to Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk is not foreseen

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or the substances contained (Annex XVII EC Reg. 1907/2006): not applicable Substances in Candidate list (art. 59 EC Reg. 1907/2006): the product does not contain SVHC in percentage = a 0.1 %.

Regulation (EC) 648/04: see point 2.2 Regulation (EU) 528/2012: see point 2.2 Regulation (EU) 1169/2011: see point 2.2 Regulation (EU) 1308/2013; see point 2.2 Regulation (EC) 1333/2008; see point 2.2 Regulation (EC) 1332/2008; see point 2.2 Seveso category:

E1 - ENVIRONMENTAL HAZARDS

REGULATION (EU) No 1357/2014 - waste:

HP8 - Corrosive HP14 - Ecotoxic

15.2. Chemical safety assessment

Chemical safety assessments were carried out for the following substances:

Sodium hydroxide Sodium hypochlorite Amines, C12-14 alkyldimethyl, N-oxides

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 1.2. Relevant identified uses of the substance or mixture and uses advised against

Description of hazard statements set out in paragraph 3

H290 = May be corrosive to metals.

H314 = Causes severe skin burns and eye damage.

H318 = Causes serious eye damage.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

H302 = Harmful if swallowed.

H315 = Causes skin irritation.

H411 = Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008: Calculation method

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.

Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seg.

Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

20 / 21

In conformity to Regulation (EU) 2020/878

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable n.d.: not available

ADR: Accord europèen relative au transport International des merchandises dangereuses par route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimat
BFC: BioconCentration Factor
BOD: Biochemical Oxigen Demand
CAS: Chemical Abstract Service number

CAP: Centre AntiPoison

CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified

Chemical Substances)

CL50/LC50: Lethal Concentration 50

DL50/LD50: Lethal Dose 50 COD: Chemical Oxygen Demand DNEL: Derived No Effect Level

EC50: half maximal Effective Concentration

ERC: Enviroment Release Classes

EU/UE: European Union

IATA: International Air Transport Association ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods code

Kow: Octanol water partition coefficient NOEC: No Observed Effect Concentration OEL: Occupational Exposure Limit

PBT: Persistent Bioaccumulative and Toxic

PC: Product Categories

PNEC: Predicted No Effect Concentration

PROC: Process Categories

RID: Règlement concernent le transport International ferroviaire des merchandises dangereuses (Regulations

concerning International rail transport of dangerous goods)

STOT: Target Organ Systemic Toxicity STOT (RE): Repeated Exposure STOT (SE): Single Exposure STP: Sewage Treatment Plants

SU: Sector of Use

SVCH: Substance of Very High Concern

TLV: Threshold Limit Value

vPvB: Verv Persistent Verv Bioaccumulative

References and Sources:

- ECHA Registered Substances:

https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

- SDS raw material supplier
- GESTIS International Limit Value: http://limitvalue.ifa.dguv.de

This msds was made in good faith by technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.



SANIFOAM

Issued on 03/24/2025 - Rel. # 12 on 03/24/2025

21 / 21

In conformity to Regulation (EU) 2020/878

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: documental updating

SUMI

Safe Use of Mixtures Information





AISE_SUMI_IS_7_4_G

Version 1.1, August 2018

Industrial spraying; Automated task; Open system; Long term

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial spraying products. This Safe Use Information is based on the AISE_SWED_IS_7_4.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves and eye protection.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health	
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI

Safe Use of Mixtures Information





AISE_SUMI_IS_8b_1

Version 1.1, August 2018

Transfer and dilution of concentrated product by using dedicated dosing system

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the AISE_SWED_IS_8b_1_L and AISE_SWED_IS_8b_1_S

Operational Conditions

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves.
personal protective equipment (PPE), hygiene and health	See section 8 of the SDS of this product for specifications.
evaluation	Training of workers in valeties to preser use and maintenance of DDFs
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI

Safe Use of Mixtures Information





AISE_SUMI_PW_8a_1_G

Version 1.1, August 2018

Transfer of product to a container (bottle/bucket/machine)

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to professional uses where the product is transferred to or diluted in a container, such as a dispenser, bottle or bucket. Safe Use Information is based on the AISE_SWED_PW_8a_1_L and AISE_SWED_PW_8a_1_S.

Operational Conditions

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI

Safe Use of Mixtures Information





AISE_SUMI_PW_11_3_G

Version 1.1, August 2018

Professional uses; Spraying

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to professional uses of products in a spraying application. This Safe Use Information is based on the AISE_SWED_PW_11_3.

Operational Conditions

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
Process conditions	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Risk Management Measures

Measures related to	Wear suitable gloves and eye protection.	
personal protective	See section 8 of the SDS of this product for specifications.	
equipment (PPE),		
hygiene and health		
evaluation		
	Training of workers in relation to proper use and maintenance of PPEs	
	must be ensured.	
Environmental	Prevent that undiluted product reaches surface waters.	
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use	
	resulting in release to municipal sewage treatment plant.	

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#12 03/24/2025

Use description Product name	Industrial spraying[PROC7], Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b] Not industrial spraying[PROC11], Transfer of substance or mixture (charging and ischarging) at not dedicated facilities IPROC8al SANIFOAM
Classification of the product (100%)	H290 - May be corrosive to metals H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H400 - Very toxic to aquatic life. H411 - Toxic to aquatic life with long lasting effects. EUH031 - Contact with acids liberates toxic gas (Cl2).
Classification of the diluted product (maximum use concentration)	At maximux concentration of use (6%) the product is classified: H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage.H412 - Harmful to aquatic life with long lasting effects.
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection. At work do not eat or drink.
Handling of the diluted product	Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection At work do not eat or drink.
DPI required concentrated use, spillage)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluited product	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear gloves, mask and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved
Diluited product	Wear gloves, mask and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.