



# LUBISAN Super Dry

.....  
 High performance lubricant with a synthetic basis for conveyor belts  
 .....

## → DESCRIPTION

**Lubisan Super Dry** is a high performance, synthetic, liquid lubricant for conveyor belts of containers for liquid products in the food, cosmetic and pharmaceutical sectors.

**Lubisan Super Dry** is used for the transportation of glass, PET, aluminium and tinned plate containers. It is supplied diluted with average long intervals between a spraying and the next one.

**Lubisan Super Dry** is scarcely sensitive to the dilution water hardness and it enables to enormously reduce the water consumption, sensibly reducing production costs.

## → TECHNICAL CHARACTERISTICS

Physical appearance: Yellow clear liquid  
 pH (0,6% solution):  $7,5 \pm 0,5$   
 pH:  $4,5 \pm 0,5$   
 Relative density at 20°C:  $1 \pm 0,05$   
 Viscosity at 20°C: <10 cps  
 Phosphor content (P) 1% sol.:  $5 \pm 1$  mg/l

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

## → INSTRUCTIONS FOR USE\*

The supply of **Lubisan Super Dry** should be carried out with the help of high precision centralized equipments, such as Lubimatic Multicontrol, by dividing the equipment into different areas in the case or particularly long or complex lines and by using nozzles with a fan spraying. The usage concentration is between 0,3 and 0,6%, according to the running speed of the lines, with average long stop times (Off). The compatibility with the packaging materials should be tested before the formulation is applied.

## → FIELDS OF APPLICATION

For the lubrication of conveyor belts.





# LUBISAN Super Dry

## → COMPATIBILITY OF THE FORMULATION

**Lubisan Super Dry** is compatible with most material normally present in food, cosmetic and pharmaceutical industries, if used according to the producer's indications. In case of doubt, carry out a test on the single material before using the product.

## → PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures. Consult the Material Safety Data Sheet.

## → TITRATION METHOD

Available on demand.

## → PACKAGING

25 kg net drums.  
200 kg net drums.  
1000 kg net IBC.

\*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.

