



FOAM P

.....
 Acid descaling foam detergent

→ DESCRIPTION

Foam P is an acid foam detergent to be used for the periodical or daily treatment of surfaces present in bottling industries, in the dairy field and in general in the food industry and the zoo-technical sector. The formulation is also ideal for the removal of protein dirt present in the fish sector.

Foam P is able to effectively remove different kinds of inorganic contamination (limestone) present on surfaces. The excellent hanging power on vertical surfaces and a quick rinsing make its utilization easier.

Foam P can be applied with a wide range of supply equipments (Easyfoam P, Combifoam, Foamlance, centralized systems, etc. ...).

→ TECHNICAL CHARACTERISTICS

Physical appearance: clear green liquid

pH: < 2

pH (6% solution at 20°C): < 2

Relative density at 20°C: 1,15 ± 0,05

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

→ INSTRUCTIONS FOR USE*

Pre-wash with water, followed by the foam application of **Foam P** directly on the surfaces to be treated, at a concentration between 3 and 6%, according to the kind of dirt and the contamination degree. Use at room temperature and on not warm surfaces. After 10-15' of contact carry out a careful final rinsing with drinking-water to remove any possible trace of washing solution. Anyway avoid prolonged contact times with surfaces (> 1 hour).

→ FIELDS OF APPLICATION

Foam P can be applied for the acid cleaning of walls, floors, external side of equipments and lines, tables and conveyor belts, storage tanks.





FOAM P

→ COMPATIBILITY OF THE FORMULATION

Foam P is compatible with most material normally present in food industries, if used according to the producer's indications. It may be used with care even on aluminium. In case of doubt, carry out a test on the single material before using the product.

→ PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures or and strong light sources. Consult the Material Safety Data Sheet.

→ TITRATION METHOD

Available on demand.

→ PACKAGING

25 kg net drums.
1200 kg net IBC.

*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.

